



GMCO HEAVY DUTY INDUSTRIAL 316 STAINLESS STEEL FERRULES

2619 Lidstone
Houston, TX 77023
800-600-3074
713-928-2606
Fax: 713-928-5873



GMCO Heavy Duty Stainless Steel Ferrules are constructed to the same standards as GMCO Heavy Duty Carbon Steel Industrial Ferrules but are designed to provide the ultimate in external environmental corrosion and chemical resistance. These fittings are used in conjunction with GMCO Heavy Duty Industrial Stainless Stems and provide permanent attached hose couplings for the harshest environments. Ferrules are kept in stock in stainless steel 316 in sizes from 2" through 6". Pricing on request for larger hoses and other grades of stainless steel. couplings can be crimped or swaged for ease of installation.

Hose Applications: Acid, Chemical, Salt Water, Water Jetting, Tank Truck, Material Handling, Multi Purpose Hose.

HOSE I.D.	HOSE O.D. SIZE RANGE	WORKING PRESSURE PSI	PART NUMBER	FERRULE SIZE			ACTUAL FERRULE WALL THICKNESS	WEIGHT LBS
				O.D.	I.D.	LENGTH		
2"	2 1/2" to 2 5/8"	800	4016+32A	3	2 3/4	3 1/2	.125	1.0
	2 5/8" to 2 13/16"	800	4016+32F	3 1/8	2 7/8	3 1/2	.125	1.0
2 1/2"	3" to 3 1/8"	800	4016+40A	3 1/2	3 1/4	4 1/4	.125	1.5
	3" to 3 3/8"	800	4016+40C	4	3 9/16	4 1/4	.226	2.8
	3 1/8" to 3 5/8"	800	4016+40B	4	3 3/4	4 1/4	.125	1.5
3"	3 1/2" to 3 5/8"	800	4016+48A	4	3 3/4	5	.125	1.8
	3 5/8" to 3 7/8"	800	4016+48B	4 1/2	4	5	.237	3.8
	3 7/8" to 4"	800	4016+48C	4 1/2	4 1/8	5	.187	3.0
	4" to 4 1/8"	800	4016+48D	4 1/2	4 1/4	5	.125	2.0
4"	4 1/2" to 4 3/4"	500	4016+64A	5 1/4	4 7/8	5 1/2	.187	3.0
	4 3/4" to 4 15/16"	500	4016+64B	5 9/16	5 1/16	5 1/2	.258	6.0
	4 15/16" to 5 1/16"	500	4016+64C	5 9/16	5 3/16	5 1/2	.187	5.0
	5 1/8" to 5 3/8"	500	4016+64E	6	5 1/2	5 1/2	.250	5.8
5"	5 3/4" to 6"	500	4016+80A	6 5/8	6 1/8	6 7/8	.250	8.7
6"	6 3/4" to 7"	500	4016+96E	7 1/2	7 1/8	7 1/2	.187	8.0
	7 1/8" to 7 3/8"	500	4016+96B	8	7 1/2	7 1/2	.250	12.3
	7 3/8" to 7 9/16"	500	4016+96C	8 3/16	7 11/16	7 1/2	.250	12.3

See SWAGE-IT HEAVY DUTY INDUSTRIAL HOSE STEMS for compatible stems.