



GMCO HEAVY DUTY INDUSTRIAL CARBON STEEL FERRULES

2619 Lidstone
Houston, TX 77023
800-600-3074
713-928-2606
Fax: 713-928-5873



GMCO Heavy Duty Industrial Ferrules are used in conjunction corresponding stems to provide a permanent end connection to rubber industrial hoses for use in the toughest applications. Constructed of extra thick carbon steel, GMCO Heavy duty swage ferrules are longer, heavier and have deeper grooves than most swage ferrules on the market. This allows hose fabricators to stock less ferrules while covering a larger range hose sizes and pressure ratings while maximizing end pull capability. All GMCO swage ferrules are zinc plated chromate finish to provide years of trouble free service.

George Myer also has the largest in stock size range of swage fittings in the industry, covering sizes for 2" through 12. Couplings can be crimped or swaged for ease of installation.

Hose Applications: Tank Truck, Chemical, Mud Suction, OS&D, Oil discharge, Frac-Tank, Water discharge, Water suction, Water Jetting, Hot Tar & Asphalt, Material handling, Textile Air Hose, Wire Air Hose, Petroleum, Marine, Dredge and Multi Purpose Hose.

HOSE I.D.	HOSE O.D. SIZE RANGE	WORKING PRESSURE PSI	PART NUMBER	FERRULE SIZE			ACTUAL FERRULE WALL THICKNESS	WEIGHT LBS
				O.D.	I.D.	Length		
2"	2 1/2" to 2 5/8"	800	4000+32A	3	2 3/4	3 1/2	.125	1.0
	2 5/8" to 2 7/8"	800	4000+32B	3 1/4	3	3 1/2	.125	1.0
	2 7/8" to 3 1/8"	800	4000+32C	3 1/2	3 1/4	3 1/2	.125	1.0
2 1/2"	3" to 3 1/8"	800	4000+40A	3 1/2	3 1/4	4 1/4	.125	1.5
	3" to 3 3/8"	800	4000+40C	4	3 9/16	4 1/4	.226	2.8
	3 1/8" to 3 5/8"	800	4000+40B	4	3 3/4	4 1/4	.125	1.5
3"	3 1/2" to 3 5/8"	800	4000+48A	4	3 3/4	5	.125	1.8
	3 5/8" to 3 7/8"	800	4000+48B	4 1/2	4	5	.237	3.8
	3 7/8" to 4"	800	4000+48C	4 1/2	4 1/8	5	.187	3.0
	4" to 4 1/8"	800	4000+48D	4 1/2	4 1/4	5	.125	2.0
	4 1/8" to 4 1/4"	800	4000+48E	5	4 1/2	5	.250	5.0
4"	4 1/2" to 4 3/4"	500	4000+64A	5 1/4	4 7/8	5 1/2	.187	3.0
	4 3/4" to 4 15/16"	500	4000+64B	5 9/16	5 1/16	5 1/2	.258	6.0
	4 15/16" to 5 1/16"	500	4000+64C	5 9/16	5 3/16	5 1/2	.187	5.0
	5 1/8" to 5 3/8"	500	4000+64E	6	5 1/2	5 1/2	.250	5.8
	5 1/8" to 5 1/2"	500	4000+64F	6	5 5/8	5 1/2	.187	4.3
5"	5 3/4" to 6"	500	4000+80A	6 5/8	6 1/8	6 7/8	.250	8.7
	6" to 6 3/8"	500	4000+80B	7	6 1/2	6 5/8	.250	7.8
6"	6 3/4" to 7"	500	4000+96E	7 1/2	7 1/8	7 1/2	.187	8.0
	7 1/8" to 7 3/8"	500	4000+96B	8	7 1/2	7 1/2	.250	12.3
	7 3/8" to 7 9/16"	500	4000+96C	8 3/16	7 11/16	7 1/2	.250	12.3
	7 5/8" to 8"	500	4000+96D	8 5/8	8 1/8	7 1/2	.250	10.8
8"	9" to 9 3/8"	400	4000+128A	10	9 1/2	8 1/2	.250	16.9
	9 1/2" to 9 3/4"	400	4000+128C	10 3/8	9 7/8	8 3/8	.250	16.5
	9 7/16" to 10 1/8"	400	4000+128B	10 3/4	10 1/4	8 3/8	.250	17.0

10"	10 1/2" to 11 1/4"	300	4000+160C	12	11 1/2	10 1/2	.250	23.5
	11 1/4" to 12 1/8"	300	4000+160A	12 3/4	12 1/4	10 1/2	.250	26.0
	12 1/8" to 13"	300	4000+160G	14	13 1/4	10 1/2	.375	45.0
12"	13" to 13 3/8"	300	4000+192A	14	13 3/8	12 1/2	.312	42.0
	13 7/16" to 14 3/8"	300	4000+192B	15	14 1/4	12 1/2	.375	54.0
<i>See SWAGE-IT HEAVY DUTY INDUSTRIAL HOSE STEMS for compatible stems.</i>								

© George Myer Company
