



GMCO HEAVY DUTY INDUSTRIAL SMOOTH CARBON STEEL FERRULES

2619 Lidstone
Houston, TX 77023
800-600-3074
713-928-2606
Fax: 713-928-5873



GMCO Heavy Duty Smooth Ferrules are offered to provide an economical alternative for low pressure applications such as tank truck hose and other hose applications generally less than 250 psi. Available from stock in both carbon steel and stainless steel 316. Couplings can be crimped or swaged for ease of installation.

Hose Applications: Tank Truck, Chemical, Mud Suction, OS&D, Oil Discharge, Water Discharge, Water Suction, Material Handling, Petroleum, Marine, and Multi Purpose Hose.

| HOSE ID | HOSE O.D. SIZE RANGE | WORKING PRESS. PSI | PART NUMBER | FERRULE SIZE | | | ACTUAL FWT | WT LBS. |
|---------|----------------------|--------------------|-------------|--------------|-------|-------|------------|---------|
| | | | | O. D. | I. D. | LG. | | |
| 2" | 2 1/2 - 2 5/8 | 400 | 4000FS+32-1 | 3 | 2 3/4 | 3 1/2 | 0.125 | 1.2 |
| | 2 5/8 - 2 3/4 | 400 | 4000FS+32-2 | 3 1/8 | 2 7/8 | 3 1/2 | 0.125 | 1.3 |
| | 2 3/4 - 2 7/8 | 400 | 4000FS+32-3 | 3 1/4 | 3 | 3 1/2 | 0.125 | 1.4 |
| 3" | 3 1/2 - 3 5/8 | 250 | 4000FS+48-1 | 4 | 3 3/4 | 5 | 0.125 | 1.9 |
| | 3 5/8 - 3 3/4 | 250 | 4000FS+48-2 | 4 1/8 | 3 7/8 | 5 | 0.125 | 2.1 |
| | 3 3/4 - 3 7/8 | 250 | 4000FS+48-3 | 4 1/4 | 4 | 5 | 0.125 | 2.3 |
| 4" | 4 5/8 - 4 3/4 | 250 | 4000FS+64-1 | 5 1/4 | 4 7/8 | 5 1/2 | 0.187 | 4.8 |
| | 4 3/4 - 4 7/8 | 250 | 4000FS+64-2 | 5 1/4 | 5 | 5 1/2 | 0.125 | 3 |
| | 4 7/8 - 5 | 250 | 4000FS+64-3 | 5 1/2 | 5 1/8 | 5 1/2 | 0.187 | 5.1 |

© George Myer Company